

EVERCOAT®

THE #1 POLYESTER FINISHING PUTTY ON THE MARKET TODAY!



- Superior solvent hold-out reduces primer “abuse” saving time and money
- Spreads smoothly, easily filling grind marks, pinholes and other minor imperfections
- Reduces rework with less post-repair shrinking, ringing or body waves
- NEW 16 fl. oz. pouch (#412) that minimizes waste

evercoat.com

METAL GLAZE®

Polyester Finishing and Blending Putty

DESCRIPTION:

METAL GLAZE is a two-part polyester finishing and blending putty that does much more than just fill pinholes, grind marks and other minor imperfections. Formulated with ZNX-7®, Metal Glaze has superior adhesion on all metal substrates, SMC and O.E.M. paint. Metal Glaze has superior solvent hold-out that reduces the number of coats of primer needed to cover each repair. Shops that use Metal Glaze on every repair save time and money because...

- Primer no longer needs to be "abused" to cover up body work imperfections
- Rework is reduced with less post-repair shrinking, ringing or body waves
- It takes less effort to finish sand with 240 or 320 grit for a smoother finish

APPROVED SUBSTRATES:

Properly prepared...

- Body Filler
- Steel
- Galvanized
- Rigid to semi-rigid fiberglass and thermo-set plastics
- For flexible plastics, use POLY-FLEX™ Flexible Polyester Glazing Putty

TECHNICAL DATA:

Appearance	Light Green Liquid
VOC	Packaged: 1.69 lbs/gal (203 g/L) Applied: 0.49 lbs/gal (59 g/L)
Gel Time	4-5 min.
Sand Time	25-30 min.
Corrosion Resistance	Excellent

NOTE: Properties are typical values and should not be considered as sales specifications. Physical Testing performed @ ~77°F(25°C)



Part No.	Size	Units/Case
100412-New	16 fl. oz. Pouch	6
100415	24 fl. oz. Tube	6
100416	30 fl. oz. Pump	6