MODERN CLASSIKK® Kindig®

POWERED BY sikkens

PREMIUM GREY PRIMER
TECHNICAL DATA SHEET

NORTH AMERICA



PROGRAMMED SYSTEM TECHNIQUE (PST)
MODERN CLASSIKK PREMIUM GREY PRIMER

Modern® Classikk Premium Grey Primer is a dependable, low-VOC primer surfacer that offers excellent filling, easy sanding, and fast dry times. This advanced surfacer system can also be used as a wet-on-wet primer sealer with a simple change to the mixing ratio. It is suitable for even the finest of restorations.

SAFETY CONSIDERATIONS

- Use suitable personal protection; AkzoNobel recommends the use of a fresh air supply respirator

By Volume

MIX	AS A SURFACER
3	• Premium Grey Primer
1	• Premium Primer Hardener
+10%	• Premium Primer Reducer LV

MIX	AS A SEALER
2	• Premium Grey Primer
1	• Premium Primer Hardener
+20%	• Premium Primer Reducer LV

Note: In VOC regulated markets, Premium Grey Primer mixed as a sealer is only compliant in Canada.

SURFACER – FLASH AT 70°F (21°C)

- 5-10 minutes between coats
- 5-10 minutes before force-dry

SEALER – FLASH AT 70°F (21°C) BEFORE TOPCOAT

- 15 minutes, minimum

SURFACER – DRY TO SAND – 3 COATS

- 4 hours at 70°F (21°C)
- 45 minutes at 140°F (60°C)

SEALER – MAXIMUM TIME TO RECOAT

- 4 hours at 70°F (21°C)

Note: If recoat time is exceeded, sealer must be sanded prior to topcoat application.

Read complete TDS for spray gun, application and recoatability information as well as detailed product information.

AkzoNobel
1845 Maxwell Drive | Troy, MI 48084 | www.modernclassikk.com
© 2026 Akzo Nobel N.V. All rights reserved. (05/26)

AkzoNobel