
SECTION 1: Identification**1.1 Product identifier**

Product name Custom Shop Premium 1K Acrylic Non-Sanding Primer Sealer Paint, Color Black

Product number CUS NSPS1981

1.2 Other means of identification

Gray 1K Acrylic Sealer /Surfacer

1.3 Recommended use of the chemical and restrictions on use

Identified Product Uses: Automotive Refinish. For industrial use only.

1.4 Supplier's details

Name Custom Shop
Address 6251 Howdy Wells Ave
Las Vegas, NV 89115
USA

Telephone 858-909-2110

1.5 Emergency phone number(s)

Chemtrec: 800-424-9300

SECTION 2: Hazard identification**General hazard statement**

Hazard statement(s): Highly flammable liquid and vapor. Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs (kidneys) through prolonged or repeated exposure. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.

Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Suspected of damaging fertility or the unborn child. May cause damage to organs (Liver, kidneys and Lungs) through prolonged or repeated exposure. Causes skin irritation. Causes serious eye irritation.

2.1 Classification of the substance or mixture**GHS classification in accordance with: (US) OSHA (29 CFR 1910.1200)**

- Flammable liquids, Cat. 1
- Eye damage/irritation, Cat. 2A
- Sensitization, skin, Cat. 1B
- Toxic to reproduction, Cat. 1B
- Specific target organ toxicity (repeated exposure), Cat. 2
- Specific target organ toxicity (single exposure), Cat. 3
- Skin corrosion/irritation, Cat. 2

CUS NSPS1981 1K BLACK NON-SANDING PRIMER SEALER SAFETY DATA SHEET

2.2 GHS label elements, including precautionary statements

Pictogram



Signal word

Warning

Hazard statement(s)

H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H360	May damage fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water/...
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor/.../ if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see ... on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use ... to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to ...

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

2.3 Other hazards which do not result in classification

Precautionary statement(s)

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. For large container, ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lightning equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe mist, vapors and spray. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye and face protection. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

1. Component 1 (trade secret)*

Concentration 10.5 - 15.71 % (weight)

- Flammable liquids, Cat. 3
- Acute toxicity, inhalation, Cat. 4
- Acute toxicity, dermal, Cat. 4
- Skin corrosion/irritation, Cat. 2
- Eye damage/irritation, Cat. 2A
- Aspiration hazard, Cat. 1

H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H373	May cause damage to organs [organs] through prolonged or repeated exposure [route]

2. Titanium dioxide (airborne, unbound particles of respirable size)

Concentration 10 - 18 % (weight)
CAS no. 13463-67-7

3. Polyphosphoric acid

Concentration 0.01 - 0.015 % (weight)
CAS no. 8017-16-1

4. Methoxyisopropyl acetate

Concentration 0.07 - 0.09 % (weight)
EC no. 203-603-9
CAS no. 108-65-6
Index no. 607-195-00-7

- Flammable liquids, Cat. 3

H226 Flammable liquid and vapor

5. C9-10 aromatic hydrocarbons

Concentration 0.05 - 0.08 % (weight)
CAS no. 64742-95-6

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

6. Fatty acids, castor-oil, caustic-oxidized, distn residues, esters with ammonia-ethylene oxide reaction product distn residues, compds with diethylenetriamine and triethylenetetramine

Concentration 0.15 - 0.17 % (weight)
CAS no. 113669-97-9

7. Hydroxyl Acrylate Resin

Concentration 25 – 30 % (weight)
CAS no. 9065-11-6

8. Ethylbenzene

Concentration 0.15 – 0.19 % (weight)
EC no. 202-849-4
CAS no. 100-41-4
Index no. 601-023-00-4

- Flammable liquids, Cat. 2
- Acute toxicity, inhalation, Cat. 4
- Specific target organ toxicity (repeated exposure), Cat. 2

H225 Highly flammable liquid and vapor
H332 Harmful if inhaled

9. Talc

Concentration 5 - 10 % (weight)
EC no. 238-877-9
CAS no. 14807-96-6

10. 4-CHLORO-ALPHA,ALPHA,ALPHA-TRIFLUOROTOLUENE

Concentration 20 - 25 % (weight)
CAS no. 98-56-6
Index no. 604-014-00-3

H226 Flammable liquid and vapor
H315 Causes skin irritation
H319 Causes serious eye irritation
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
H351 Suspected of causing cancer [route]
H411 Toxic to aquatic life with long lasting effects

11. Methyl acetate

Concentration 25 - 30 % (weight)
EC no. 201-185-2
CAS no. 79-20-9
Index no. 607-021-00-X

- Flammable liquids, Cat. 2
- Specific target organ toxicity (single exposure), Cat. 3
- Serious eye damage/eye irritation, Cat. 2

H225 Highly flammable liquid and vapor
H319 Causes serious eye irritation
H336 May cause drowsiness or dizziness

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

12. Black Powder

Concentration 0.04 - 0.06 % (weight)
CAS no. 1333-86-4

Trade secret statement (OSHA 1910.1200(i))

Any concentration shown as a < % weight is to protect confidentiality or is due to batch variation.
There are no additional ingredients within the current knowledge of the supplier.
Concentrations are classified and although require reporting in this section.

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).
If inhaled	Call a poison center or doctor if you feel unwell. Acute and delayed symptoms and effects: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.
In case of skin contact	Wash with plenty of soap and water for at least 15 minutes. Call a poison center or doctor if you feel unwell. Acute and delayed symptoms and effects: May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.
In case of eye contact	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. Acute and delayed symptoms and effects: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.
If swallowed	If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available. Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately. Skin contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately. Inhalation: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately. Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately. Symptoms: We can observe headaches, nausea, vomiting and dizziness. Decreased concentration and memory, sleep disturbances, irritability and

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

muscular aches. Cough, breathing pain, eye redness. Redness, flaking and cracking of the skin. Euphoria and disorientation.

Effects (acute or delayed): Inhalation of high concentrations vapors can cause narcotic effect. May cause irritation of eyes and respiratory tract.

Personal protective equipment for first-aid responders

Obtain exposure level time to understand saturation of vapors potentially inhaled.

4.2 Most important symptoms/effects, acute and delayed

Effects: (acute or delayed): Inhalation of high concentrations vapors can cause narcotic effect. May cause irritation of eyes and respiratory tract. May cause skin irritation. Following repeated or prolonged contact, it has a degreasing effect on the skin. In high concentration, can cause depression of the central nervous system. May cause kidney damage.

4.3 Indication of immediate medical attention and special treatment needed, if necessary

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Specific hazards arising from the chemical

Not known

5.3 Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Use personal protection recommended in Section 8.

As an immediate precautionary measure, isolate spill or leak area in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate enclosed areas.

6.2 Environmental precautions

Keep out of drains, sewers, ditches, and waterways.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

7.2 Conditions for safe storage, including any incompatibilities

Store below 120F to avoid building vapor pressure in container. Keep container tightly closed. Keep out of the reach of children.

Specific end use(s)

Apart from the uses mentioned in section 1 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. Component 1 (trade secret)*

PEL (Inhalation): 435 mg/m³ (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 100 ppm, (ST) 150 ppm, (C) 300 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 100 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 100 ppm, (ST) 150 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

2. Charcoal powder (CAS: 1333-86-4)

PEL (Inhalation): 3.5 mg/m³ (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 3.5 mg/m³ (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 3.5 mg/m³ (without PAHs); when PAHs are present, NIOSH considers carbon black to be a potential occupational carcinogen., See Appendix A, see Appendix C (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

3. Ethylbenzene (CAS: 100-41-4)

PEL (Inhalation): 100 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 435 mg/m³ (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 100 ppm, (ST) 125 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 100 ppm, (ST) 125 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

TLV® (Inhalation): 20 ppm; USA (ACGIH)

OSHA Annotated Table Z-1, www.osha.gov

4. Talc (CAS: 14807-96-6)

PEL (Inhalation): See Annotated Z-3 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): See Annotated Z-3 mg/m³ (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): See Annotated Z-3 (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): See Annotated Z-3 (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): See Annotated Z-3 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

PEL (Inhalation): See Annotated Z-3 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): See Annotated Z-3 (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): See Annotated Z-3 (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov

5. Methyl acetate (CAS: 79-20-9)

PEL (Inhalation): 200 ppm (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 610 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 200 ppm, (ST) 250 ppm (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 200 ppm, (ST) 250 ppm (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov

8.2 Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Half mask or full face respirators with appropriate cartridge to eliminate inhalation of vapors and/or dust.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Safety glasses with side-shields and/or full face respirators.

Skin protection

Protective gloves, such as nitrile gloves. See HMIS rating for recommended Personal Protection

Body protection

Wear protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Thermal hazards

No data available.

Environmental exposure controls

Do not let product enter drains. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.)	Liquid
Odor	Organic Solvent
Odor threshold	No data available.
pH	No data available
Melting point/freezing point	-76F
Initial boiling point and boiling range	133.10F
Flash point	<0°F TCC
Evaporation rate	>1 (ether=1)
Flammability (solid, gas)	High
Upper/lower flammability limits	Upper Limit: 11% at 25 °C Lower Limit: 1.63% at 25 °C
Upper/lower explosive limits	No data available.
Vapor pressure	>45 mm Hg at 20 °C
Vapor density	No data available.
Relative density	1.192
Solubility(ies)	Insoluble in water
Partition coefficient: n-octanol/water	No data available.
Auto-ignition temperature	No data available
Decomposition temperature	No data available.
Viscosity	No data available.
Explosive properties	No data available.
Oxidizing properties	No data available.

Other safety information

Wt. % Solids: 34.46
Vol. % Solids: 25.05
Wt. % Volatiles: 15.31
VOC Content (%): 2.1 lb/gal

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended conditions of storage and handling

10.2 Chemical stability

This product is chemically stable under normal conditions of use

10.3 Possibility of hazardous reactions

No dangerous or polymerization reactions will not occur under normal conditions of use. Danger of explosion when heated.

10.4 Conditions to avoid

Contact with incompatible materials. Sources of ignition. Exposure to heat.

10.5 Incompatible materials

Plastics, Acids, Bases, Nitrates, Strong oxidizing agents

10.6 Hazardous decomposition products

XYLENES (MIXED): Carbon oxides
Hydrocarbons
Aldehydes

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

Methyl Acetate
Carbon monoxide (CO), Carbon dioxide (CO)

SECTION 11: Toxicological information

Information on toxicological effects

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Components:

----Methyl Acetate----

Central nervous system (CNS)

Symptoms (including delayed and immediate effects):

Inhalation: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Ingestion: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Component 1: Acute inhalation toxicity: LC50 (rat, male): 6700ppm, Exposure time: 4h, Assessment: The component/mixture is moderately toxic after short term inhalation
Acute dermal toxicity: LD50 (Rabbit): 1,700 mg/kg Assessment: the component/mixture is moderately toxic after single contact with skin

PCBTF

WARNING! This product can expose you to chemicals including Parachlorobenzotrifluoride (PCBTF), which is/are known to the State of California to cause cancer.

// ----- From the Suggestion report (08/07/2023, 7:49 AM) ----- //
ATE (inhalation, gaseous) of mixture: 28644.18 ppmv

Skin corrosion/irritation

May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Component 1: Species: Rabbit
Exposure time: 24h
Result: Irritating to skin

PCBTF-98-56-6:
Test Type: lymph node assay
Species: Mouse
Result: The product is a skin sensitiser, sub-category 1B

Methyl acetate
LD50 > 5 g/kg (Rat) LD50 > 5 g/kg (Rabbit) LC50 > 49000 mg/m3
(Rat) 4 h

Serious eye damage/irritation

May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

METHYL ACETATE

Vapors can be Irritating to eyes and throat

Component 1: Species: Rabbit
Result: Irritating to eyes

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

Respiratory or skin sensitization

No data available.

Methyl Acetate:

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Component 1: May be fatal if swallowed and enters airways.

PCBTC

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin

Carcinogenicity

This product is or contains a component that has been reported to be carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Component 1: IARC Group 2B: Possibly carcinogenic to humans

100-41-4: Ethylbenzene

98-82-8 Cumene

Summary of evaluation of the CMR properties

No data available.

STOT-single exposure

-----XYLENE-----

Specific target organ toxicity - single exposure

May cause respiratory irritation. - Respiratory system

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure. - Central nervous system, Liver, Kidney

Aspiration hazard

STOT-repeated exposure

----PCBTF----

Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity: Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity: Assessment: The substance or mixture has no acute dermal toxicity

-----METHYL ACETATE-----

Delayed and immediate effects as well as chronic effects from short and long-term exposure

-----XYLENE-----

**CUS NSPS1981
1K BLACK NON-SANDING PRIMER SEALER
SAFETY DATA SHEET**

No data available

Aspiration hazard
No data available

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

SECTION 12: Ecological information

Toxicity

PCBTF---

98-56-6:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 3 mg/l

Exposure time: 96 h

Test Type: semi-static test

Toxicity to daphnia and other

aquatic invertebrates

: IC50 (Daphnia magna (Water flea)): 2 mg/l

Exposure time: 48 h

Test Type: semi-static test

Acute aquatic toxicity- Assessment

: Toxic to aquatic life.

Chronic aquatic toxicity- Assessment

: Toxic to aquatic life with long lasting effects.

---XYLENE---

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause respiratory irritation. - Respiratory system

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure. - Central nervous system, Liver, Kidney

---METHYL ACETATE---

Mutagenic Effects No information available

Reproductive Effects No information available. Developmental Effects No information available. Teratogenicity

No information available. STOT - single exposure Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Results of PBT and vPvB assessment

No data available

Other adverse effects

Component 1: Ozone-Depletion Potential:

Regulation: 40 CFR Protection of Environment: Part 82 Protection of Stratospheric Ozone- CAA section 602

Class I substances

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

SECTION 13: Disposal considerations

Disposal of the product

Disposal should be in accordance with applicable Federal, State and local laws and regulations. Local regulations may be more stringent than State or Federal requirements.

Disposal of contaminated packaging

Dispose of as unused product.

Waste treatment

Waste should be minimized at all times. All waste material should be disposed of with a licensed waste disposal contractor.

SECTION 14: Transport information

DOT (US)

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint Related Material

Reportable quantity (RQ):

Marine pollutant:

Poison inhalation hazard:

IMDG

UN Number: UN1263

Class: 3

Packing Group: II

EMS Number: F-E, S-E

Proper Shipping Name: Paint Related Material

IATA

UN Number: UN1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint Related Material

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Massachusetts Right To Know Components

Chemical name: Xylene (mixed isomers)

CAS number: 1330-20-7

New Jersey Right To Know Components

Common name: XYLENES

CAS number: 1330-20-7

Pennsylvania Right To Know Components

Chemical name: Benzene, dimethyl-

CAS number: 1330-20-7

Canadian Domestic Substances List (DSL)

Chemical name: Benzene, dimethyl-

CAS: 1330-20-7

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

Massachusetts Right To Know Components

Chemical name: Benzene, m-dimethyl-
CAS number: 108-38-3

New Jersey Right To Know Components

Common name: m-XYLENE see Fact Sheet # 2014 on XYLENE
CAS number: 108-38-3

Pennsylvania Right To Know Components

Chemical name: Benzene, 1,3-dimethyl-
CAS number: 108-38-3

Canadian Domestic Substances List (DSL)

Chemical name: Benzene, 1,3-dimethyl-
CAS: 108-38-3

New Jersey Right To Know Components

Common name: CARBON BLACK
CAS number: 1333-86-4

Pennsylvania Right To Know Components

Chemical name: Carbon black
CAS number: 1333-86-4

Canadian Domestic Substances List (DSL)

Chemical name: Carbon black
CAS: 1333-86-4

California Prop. 65 components

Chemical name: Carbon black (airborne, unbound particles of respirable size)
CAS number: 1333-86-4
02/21/2003 - Cancer

California Prop. 65 components

Chemical name: Titanium dioxide (airborne, unbound particles of respirable size)
CAS number:
09/02/2011 - Cancer

Canadian Domestic Substances List (DSL)

Chemical name: Polyphosphoric acids
CAS: 8017-16-1

Canadian Domestic Substances List (DSL)

Chemical name: 2-Propanol, 1-methoxy-, acetate
CAS: 108-65-6

Canadian Non-Domestic Substances List (NDSL)

Chemical name: Fatty acids, castor-oil, caustic-oxidized, distn. residues, esters with ammonia-ethylene oxide reaction product distn. residues, compds. with diethylenetriamine and triethylenetetramine
CAS: 113669-97-9

Massachusetts Right To Know Components

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

Chemical name: Ethylbenzene
CAS number: 100-41-4

New Jersey Right To Know Components

Common name: ETHYL BENZENE
CAS number: 100-41-4

Pennsylvania Right To Know Components

Chemical name: Benzene, ethyl-
CAS number: 100-41-4

Canadian Domestic Substances List (DSL)

Chemical name: Benzene, ethyl-
CAS: 100-41-4

Massachusetts Right To Know Components

Chemical name: Ethylbenzene
CAS number: 100-41-4

New Jersey Right To Know Components

Common name: ETHYL BENZENE
CAS number: 100-41-4

Pennsylvania Right To Know Components

Chemical name: Benzene, ethyl-
CAS number: 100-41-4

California Prop. 65 Components

WARNING: this product contains a chemical known in the State of California to cause cancer.
Ingredients
ethylbenzene

California Prop. 65 components

Chemical name: ETHYLBENZENE
CAS number: 100-41-4
06/11/2004 - Cancer

New Jersey Right To Know Components

Common name: TALC (NOT CONTAINING ASBESTOS FIBERS)
CAS number: 14807-96-6

Pennsylvania Right To Know Components

Chemical name: Talc
CAS number: 14807-96-6

Canadian Domestic Substances List (DSL)

Chemical name: Talc (Mg₃H₂(SiO₃)₄)
CAS: 14807-96-6

Massachusetts Right To Know Components

Enter applica

CUS NSPS1981

1K BLACK NON-SANDING PRIMER SEALER

SAFETY DATA SHEET

Canadian Domestic Substances List (DSL)

Chemical name: Benzene, 1-chloro-4-(trifluoromethyl)-
CAS: 98-56-6

New Jersey Right To Know Components

Chemical name: Benzene, 1-chloro-4-(trifluoromethyl)-
CAS: 98-56-6

SARA 311/312 Hazards

Flammable (gases, aerosols, liquids, or solids) Skin corrosion or irritation Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure) Carcinogenicity

Pennsylvania Right To Know Components

Chemical name: Benzene, 1-chloro-4-(trifluoromethyl)-
CAS: 98-56-6

California Prop. 65 components

Chemical name: 4-CHLORO-ALPHA,ALPHA,ALPHA-TRIFLUOROTOLUENE
CAS number: 98-56-6
11/17/2021 - Cancer

New Jersey Right To Know Components

Common name: METHYL ACETATE
CAS number: 79-20-9

Pennsylvania Right To Know Components

Chemical name: Acetic acid, methyl ester
CAS number: 79-20-9

Canadian Domestic Substances List (DSL)

Chemical name: Acetic acid, methyl ester
CAS: 79-20-9

15.2 Chemical Safety Assessment

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

HMIS Rating

Health	2
Flammability	3
Physical hazard	0
Personal protection	G

NFPA Rating

Health hazard	2
Fire hazard	3
Reactivity hazard	0
Special hazard	

SECTION 16: Other information

Date of printing: 2/9/24

CUS NSPS1981 1K BLACK NON-SANDING PRIMER SEALER SAFETY DATA SHEET

Date of issue: 2/13/2023

Date of revision: na

Version 001

16.1 Further information/disclaimer

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer.