

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: KUSTOM POLY-GLAZE
 PRODUCT CODE: KPG-101

HMIS CODES: H F R P
 2*3 1

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: KUSTOM SHOP PRODUCTS
 ADDRESS: 6695 RASHA STREET
 SAN DIEGO, CA 92121-2241
 EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 (U.S) DATE PRINTED : 02/09/06
 EMERGENCY PHONE(CHEMTREC) : (703) 527-3887 (U.S) NAME OF PREPARER : N/A
 INFORMATION PHONE : (800) 672-4900

===== SECTION II - HAZARDOUS INGREDIENTS =====

INGREDIENTS	CAS NUMBER	TEL/PEL	WEIGHT(%) APPROX.
NON-FIBROUS TALC	14807-96-6	ACGIH: TWA 2mg/m3 OSHA: TLV 30 mppcf	40
STYRENE	100-42-5	OSHA PEL: 100 ppm CPEL 200 ppm ACGIH TLV: 20 ppm STEL 100 ppm See Health Hazard Information	30
ZINC SULFIDE	1314-98-3	ACGIH TLV: 10 mg/m3	10
TITANIUM DIOXIDE	13463-67-7	OSHA PEL: TWA 15mg/m3 ACGIH TLV: 10 mg/m3	10
GLASS BEADS	50815-87-7	ACGIH: TWA 10 mg/m3	10

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE(Deg F): N/A VOLATILES BY VOLUME: 20-30%
 VAPOR DENSITY: HEAVIER THAN AIR SPECIFIC GRAVITY (H2O=1): 1.16
 SOLUBILITY IN WATER: Insoluble EVAPORATION RATE: SLOWER THAN ETHER
 APPEARANCE AND ODOR: Green Smooth Paste
 V.O.C.: 285 grams/liter less exempts, 2.2 Unconsumed VOC upon curing

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT(Deg F): 89 METHOD USED: SETA
 FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: 1.1 UPPER: 6.1

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

Fight like a fuel oil fire. Cool fire exposed containers with water spray.
 Firefighters should wear OSHA/NIOSH approved self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may rupture due to buildup of steam pressure when exposed to extreme heat such as fire.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

Avoid heat, sparks, flame and other sources of ignition.

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong acids, alkalis, oxidizers.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Carbon monoxide, Carbon Dioxide and Carbon

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE EFFECTS:

Eyes: Contact with eyes can cause irritation, redness, tearing, blurred vision, and/or swelling.

Skin: Contact with skin can cause irritation, (minor itching, burning and/or redness). Dermatitis, defatting may be readily absorbed through the skin.

Inhalation: Inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and/or asphyxiation. Aspiration of material into lungs may result in chemical pneumonitis which can be fatal.

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting, diarrhea.

CHRONIC EFFECTS:

Overexposure to this material has apparently been known to cause the following effects in lab animals: central nervous system damage, eye, skin, and lung damage appendages.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: No
STYRENE WARNING:**

Styrene is listed by the IARC to be a possible carcinogen. Styrene studies have shown that styrene causes cancer in certain laboratory animals. However, there is insufficient evidence to conclude that styrene is a human carcinogen.

PRIMARY ROUTES OF EXPOSURE: skin, inhalation, eyes

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: If inhaled, remove victim from exposure to a well-ventilated area.

Make them comfortable warm, but not hot. Use oxygen or artificial respiration as required. Consult a physician.

SKIN: For skin contact, wash promptly with soap and excess water.

EYES: For eye contact, flush promptly with excess water for at least 15 minutes.

Consult a physician.

INGESTION: If ingested, do not induce vomiting. Give a victim a glass of water.

Call a physician.

===== SECTION VII - SPILL AND DISPOSAL PROCEDURES =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Ventilate area. Remove all possible sources of ignition. Avoid prolonged breathing of vapor.

Contain spill with inert absorbent.

WASTE DISPOSAL METHOD

Dispose of in accordance with local, state and federal regulations.

MARINE POLLUTION WARNING: Contains ten percent or more of marine pollutant.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Use with adequate ventilation. Avoid contact with eyes and skin. Avoid breathing vapors. Do not store the product above 100F/38C. Do not flame, cut, braze weld or melt empty containers. Keep the product away from heat, open flame and other sources of ignition. Avoid contact with strong acids, alkalis and oxidizers.

===== SECTION VIII - PROTECTION INFORMATION =====**RESPIRATORY PROTECTION**

If exposure may or does exceed occupational exposure limits, use a NIOSH approved respirator to prevent overexposure. In accordance with 29 CFR 1910.134, use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

VENTILATION

Use adequate ventilation in volume and pattern to keep TLV/PEL below recommended levels. Explosion-proof ventilation may be necessary.

PROTECTIVE GLOVES

To prevent prolonged exposure use rubber gloves; solvents may be absorbed through the skin.

EYE PROTECTION

Safety glasses and gloves with splash guards or side shields.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Wear protective clothing as required to prevent skin contact.

WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

===== SECTION IX - REGULATORY INFORMATION =====**CALIFORNIA PROPOSITION 65**

This product contains a chemical known to the State of California to cause cancer.
Silica, Crystalline (Trace) - Styrene Oxide (Trace) -

SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372.

CHEMICAL NAME	CAS NO.	%BY WT.
----------------------	----------------	----------------

Styrene	100-42-5	20-30%
---------	----------	--------

This information must be included in all MSDS's that are copied and distributed for this chemical.

TRANSPORTATION

Proper Shipping Name: STYRENE MONOMER, STABILIZED

Hazard Class: 3

Subsidiary Risk: N.A.

UN Number: UN2055

Packing Group: III

Marine Pollutant: N.A.

===== SECTION X - ABBREVIATIONS =====

IARC = International Agency for Research on Cancer
ACGIH = American Conference of Governmental Industrial Hygienists
NIOSH = National Institute of Occupational Safety and Health
TLV = Threshold Limit Value
PEL = Permissible Emission Level
DOT = Department of Transportation
NTP = National Toxicology Program
N/A = Not Available
N/E = Not Established

===== SECTION XI - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, Kustom Shop Products makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Kustom Shop Products assumes no responsibility for injury from the use of the product described herein.