
SECTION 1: Identification

1.1 Product identifier

Product name RSP DTM4200 DTM High Build Urethane Primer Surfacer
Product number RSP DTM4200
Brand Manufactured for TCP Global Corporation

1.2 Other means of identification

Gray Urethane Primer

1.3 Recommended use of the chemical and restrictions on use

Automotive Refinish. For industrial use only.

1.4 Supplier's details

Name Manufactured for TCP Global Corporation
Address 6251 Howdy Wells Ave.
Las Vegas, NV 89115
858-909 -2110

1.5 Emergency phone number(s)

Chemtrec: 800-424-3900

SECTION 2: Hazard identification

General hazard statement

Hazard statement(s): Highly flammable liquid and vapor. Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs (kidneys) through prolonged or repeated exposure. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Suspected of damaging fertility or the unborn child. May cause damage to organs (Liver, kidneys and lungs) through prolonged or repeated exposure. Causes skin irritation. Causes serious eye irritation.

2.1 Classification of the substance or mixture

GHS classification in accordance with: (US) OSHA (29 CFR 1910.1200)

- Flammable liquids, Cat. 2
- Flammable liquids, Cat. 1
- Eye damage/irritation, Cat. 2A
- Sensitization, skin, Cat. 1B
- Toxic to reproduction, Cat. 1B
- Specific target organ toxicity (repeated exposure), Cat. 2
- Specific target organ toxicity (single exposure), Cat. 3
- Skin corrosion/irritation, Cat. 2

2.2 GHS label elements, including precautionary statements

Pictogram



Signal word **Danger**

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

Hazard statement(s)

H225	Highly flammable liquid and vapor
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs [organs] through prolonged or repeated exposure [route]

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water/...
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor/.../ if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see ... on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use ... to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to ...
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

2.3 Other hazards which do not result in classification

Precautionary statement(s)

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. For large container, ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lightning equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe mist, vapors and spray. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye and face protection. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

1. Talc

Concentration 10 - 15 % (weight)

EC no. 238-877-9

CAS no. 14807-96-6

2. Titanium dioxide (airborne, unbound particles of respirable size)

Concentration 10 - 15 % (weight)

3. Black Powder

Concentration 0.2 - 0.35 % (weight)

CAS no. 1333-86-4

4. Dolomite powder

Concentration 10 - 20 % (weight)

CAS no. 471-34-1

5. Kaolin

Concentration 5 - 10 % (weight)

EC no. 310-194-1

CAS no. 1332-58-7

6. Stearalkonium bentonite

Safety Data Sheet SL-2KVHB Medium Build Gray Primer

Version: 001, Revision: 00, Supersedes: Initial, Date of issue: 2023-23-03, Printed on: 2023-23-03, p. 4 of 20

Concentration 0.4 - 0.7 % (weight)

CAS no. 130501-87-0

7. 2-Propenoic acid, 2-methyl-, polymer with ethenylbenzene and methyl 2-methyl-2-propenoate

Concentration 25 - 35 % (weight)

CAS no. 25035-81-8

8. Xylene

Concentration 8 - 12 % (weight)

EC no. 215-535-7

CAS no. 1330-20-7

Index no. 601-022-00-9

- Flammable liquids, Cat. 3

- Acute toxicity, inhalation, Cat. 4

- Acute toxicity, dermal, Cat. 4

- Skin corrosion/irritation, Cat. 2

- Eye damage/irritation, Cat. 2A

- Aspiration hazard, Cat. 1

H226 Flammable liquid and vapor

H304 May be fatal if swallowed and enters airways

H312 Harmful in contact with skin

H315 Causes skin irritation

H319 Causes serious eye irritation

H332 Harmful if inhaled

H335 May cause respiratory irritation

H373 May cause damage to organs [organs] through prolonged or repeated exposure [route]

9. Phosphoric acid

Concentration 0.2 - 0.3 % (weight)

EC no. 231-633-2

CAS no. 7664-38-2

Index no. 015-011-00-6

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

- Skin corrosion/irritation, Cat. 1B
H314 Causes severe skin burns and eye damage

10. Methoxyisopropyl acetate

Concentration 0.1 - 0.15 % (weight)
EC no. 203-603-9
CAS no. 108-65-6
Index no. 607-195-00-7
- Flammable liquids, Cat. 3
H226 Flammable liquid and vapor

11. C9-10 aromatic hydrocarbons

Safety Data Sheet SL-2KVHB Medium Build Gray Primer
Version: 001, Revision: 00, Supersedes: Initial , Date of issue: 2023-23-03, Printed on: 2023-23-03, p. 5 of 20
Concentration 0.1 - 0.15 % (weight)
CAS no. 64742-95-6

12. Acetone

Concentration 10 - 15 % (weight)
EC no. 200-662-2
CAS no. 67-64-1
Index no. 606-001-00-8
- Flammable liquids, Cat. 2
- Specific target organ toxicity (single exposure), Cat. 3
- Serious eye damage/eye irritation, Cat. 2
H225 Highly flammable liquid and vapor
H319 Causes serious eye irritation
H336 May cause drowsiness or dizziness

13. Butyl acetate

Concentration 2 - 5 % (weight)
EC no. 204-658-1
CAS no. 123-86-4
Index no. 607-025-00-1
- Flammable liquids, Cat. 3
- Specific target organ toxicity (single exposure), Cat. 3
H226 Flammable liquid and vapor
H336 May cause drowsiness or dizziness

14. DIBUTYLTIN DILAURATE

Concentration 0.02 - 0.05 % (weight)
CAS no. 77-58-7

Trade secret statement (OSHA 1910.1200(i))

Any concentration shown as a < % weight is to protect confidentiality or is due to batch variation.
There are no additional ingredients within the current knowledge of the supplier.
Concentrations are classified and although require reporting in this section.

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Inhalation: Call a poison center or doctor if you feel unwell.
Acute and delayed symptoms and effects: May cause respiratory irritation.
Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness and nose and throat pain.

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

- Skin contact:** Wash with plenty of soap and water for at least 15 minutes. Call a poison center or doctor if you feel unwell. Acute and delayed symptoms and effects: May cause skin irritation. Signs/symptoms may include localized redness, swelling and itching.
- Eye contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Signs/symptoms may include redness, swelling, pain, tearing and blurred or hazy vision.
- Ingestion:** If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available. Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately. Symptoms: We can observe headaches, nausea, vomiting and dizziness. Decreased concentration and memory, sleep disturbances, irritability and muscular aches. Cough, breathing pain, eye redness. Redness, flaking and cracking of the skin. Euphoria and disorientation.

4.2 Most important symptoms/effects, acute and delayed

Effects: (acute or delayed): inhalation of high concentrations vapors can cause narcotic effect. May cause irritation of eyes and respiratory tract. May cause skin irritation. Following repeated or prolonged contact, it has a degreasing effect on the skin. In high concentrations, can cause depression of the central nervous system. May cause kidney damage.

4.3 Indication of immediate medical attention and special treatment needed, if necessary

No specific treatment. Treat symptomatically. Contact poison control treatment specialist immediately if large quantities have been ingested or inhaled.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Specific hazards arising from the chemical

Xylene: Avoid contamination with oxidizing agents.

N-Butyl acetate: Avoid contamination with oxidizing agents.

5.3 Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Use personal protection recommended in Section 8.

As an immediate precautionary measure, isolate spill or leak area in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate enclosed areas.

6.2 Environmental precautions

Keep out of drains, sewers, ditches, and waterways.

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

7.2 Conditions for safe storage, including any incompatibilities

Store below 120°F to avoid building vapor pressure in container. Keep container tightly closed. Keep out of the reach of children.

Specific end use(s)

Apart from the uses mentioned in section 1 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. Talc (CAS: 14807-96-6)

PEL (Inhalation): See Annotated Z-3 ppm (OSHA)
OSHA Annotated Table Z-1, www.osha.gov
PEL (Inhalation): See Annotated Z-3 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov
PEL (Inhalation): See Annotated Z-3 (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov
REL (Inhalation): See Annotated Z-3 (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov

2. Charcoal powder (CAS: 1333-86-4)

PEL (Inhalation): 3.5 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov
PEL (Inhalation): 3.5 mg/m³ (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov
REL (Inhalation): 3.5 mg/m³ (without PAHs); when PAHs are present, NIOSH considers carbon black to be a potential occupational carcinogen., See Appendix A, see Appendix C (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov

3. Kaolin (CAS: 1332-58-7)

PEL (Inhalation): 15 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov
REL (Inhalation): 10 mg/m³ (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov
PEL (Inhalation): 5 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov
PEL (Inhalation): 2 mg/m³, (no asbestos, < 1% crystalline silica) (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov
REL (Inhalation): 5 mg/m³ (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov

4. Xylene (CAS: 1330-20-7)

PEL (Inhalation): 100 ppm (OSHA)
OSHA Annotated Table Z-1, www.osha.gov
PEL (Inhalation): 435 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

PEL (Inhalation): 100 ppm, (ST) 150 ppm, (C) 300 ppm (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov
REL (Inhalation): 100 ppm, (ST) 150 ppm (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov

5. Phosphoric acid (CAS: 7664-38-2 EC: 231-633-2)

PEL (Inhalation): 1 mg/m³; USA (OSHA)
OSHA Annotated Table Z-1, www.osha.gov
PEL (Inhalation): 1 mg/m³, (ST) 3 mg/m³; USA (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov
REL (Inhalation): 1 mg/m³, (ST) 3 mg/m³; USA (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov
TLV® (Inhalation): 1 mg/m³, (ST) 3 mg/m³; USA (ACGIH)
OSHA Annotated Table Z-1, www.osha.gov

6. Acetone (CAS: 67-64-1)

PEL (Inhalation): 1000 ppm (OSHA)
OSHA Annotated Table Z-1, www.osha.gov
PEL (Inhalation): 2400 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov
PEL (Inhalation): 500 ppm, (ST) 750 ppm, (C) 3000 ppm (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov
REL (Inhalation): 250 ppm (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov
TLV® (Inhalation): 250 ppm, (ST) 500 ppm; USA (ACGIH)
OSHA Annotated Table Z-1, www.osha.gov

7. Butyl acetate (CAS: 123-86-4 EC: 204-658-1)

PEL (Inhalation): 150 ppm (OSHA)
OSHA Annotated Table Z-1, www.osha.gov
PEL (Inhalation): 710 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov
PEL (Inhalation): 150 ppm, (ST) 200 ppm (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov
REL (Inhalation): 150 ppm, (ST) 200 ppm (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov
TLV® (Inhalation): 150 ppm, (ST) 200 ppm; USA (ACGIH)
OSHA Annotated Table Z-1, www.osha.gov
STEL (Inhalation): 200 ppm, 950 mg/m³ (Cal/OSHA)
California permissible exposure limits for chemical contaminants
(Title 8, Article 107)
PEL (Inhalation): 150 ppm, 710 mg/m³
California permissible exposure limits for chemical contaminants
(Title 8, Article 107)

8.2 Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Half mask or full face respirators with appropriate cartridge to eliminate inhalation of vapors and/or dust.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Safety glasses with side-shields and/or full face respirators.

Skin protection

Protective gloves, such as nitrile gloves.

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

Body protection

Wear protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Thermal hazards

No data available.

Environmental exposure controls

Do not let product enter drains. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

Appearance (physical state, color, etc.):

Physical state:	Liquid
Color:	Clear
Odor:	Organic Solvent
Odor threshold:	Not available
pH:	Not available
Melting point/freezing point:	-87°F
Boiling/condensation point	228 °F
Flash point:	Not available
Evaporation rate:	>1 (ether=1)
Flammability (solid, gas):	High
Upper/lower flammability limits	Upper limit: 9.0% at 25°C Lower limit: 5.0% at 25°C
Upper/lower explosive limits	No data available
Vapor pressure:	>10 mm Hg at 20°C
Vapor density:	No data available
Relative density:	1.403
Solubility (ies)	Insoluble in water
Partition coefficient (n-octanol/water):	Not available
Auto-ignition temperature:	>290°F
Decomposition temperature:	Not available
Viscosity (dynamic):	Not available
Explosive properties:	Not available
Oxidizing properties:	Not available

Other safety information

Wt. % Solids: 65.38
Vol. % Solids: 44.84
Wt. % Volatiles: 23.11
VOC Content (%): 13.41
Regulatory VOC: 3.34 lbs/gal (400.49 g/l)
Material VOC: 2.62 lbs/gal (336.37 g/l)

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended conditions of storage and handling

10.2 Chemical stability

This product is chemically stable under normal conditions of use

10.3 Possibility of hazardous reactions

No dangerous or polymerization reactions will not occur under normal conditions of use.

10.4 Conditions to avoid

Contact with incompatible materials. Sources of ignition. Exposure to heat.

10.5 Incompatible materials

Plastics, Acids, Bases, Nitrates, Strong oxidizing agents

Acetone: Bases, Oxidizing agents, Reducing agents, Acetone reacts violently with phosphorous oxychloride.

N-Butyl acetate: Strong oxidizing agents, Strong reducing agents, Strong bases

10.6 Hazardous decomposition products

XYLENES (MIXED): Carbon oxides

Hydrocarbons

Acetone: Other decomposition products - No data available In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Components:

Symptoms (including delayed and immediate effects):

Inhalation: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Ingestion: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

XYLENES (MIXED): Acute inhalation toxicity: LC50 (rat, male): 6700ppm, Exposure time: 4h, Assessment: The component/mixture is moderately toxic after short term inhalation

Acute dermal toxicity: LD50 (Rabbit): 1,700 mg/kg Assessment: the component/mixture is moderately toxic after single contact with skin

Acetone: LD50 Oral- Rat- Female- 5800 mg/kg

Remarks: (ECHA)

LC50 Inhalation-Rat- 4 h- 76 mg/l

Remarks: Unconscious, Drowsiness, Dizziness

LD50 Dermal-Rabbit- 20,000 mg/kg

Remarks: (IUCLID)

ACETONE

LD50 Skin - Guinea pig - 7,429 mg/kg

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER SAFETY DATA SHEET

ACETONE

LC50 Inhalation - Rat - 50,100 mg/m³ - 8 h

Remarks: Drowsiness Dizziness Unconsciousness

ACETONE

LD50 Oral - Rat - 5,800 mg/kg

Remarks: Behavioral :Altered sleep time (including change in righting reflex). Behavioral:Tremor.

Behavioral:Headache.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

ACETONE

LC50 - Oncorhynchus mykiss (rainbow trout - 5,540 mg/l - 96 h

ACETONE

LC50 - Daphnia magna (Water flea) - 8,800 mg/l - 48 hr

XYLENES (MIXED)

LC50 Inhalation - Rat - 6700 ppm - 4H

Result: Indicate results

(e.g., "LC50=28 mg/l", "LD50=2000 mg/kg")

Remarks: Other comments on conditions or results

Citation: Indicate study title, authors, journal, date, etc.

XYLENES (MIXED)

LD50 Skin - Rabbit - 1,700 mg/kg - Select Igth

(e.g., "96 h", "28 days")

Result: Indicate results

(e.g., "LC50=28 mg/l", "LD50=2000 mg/kg")

Remarks: Other comments on conditions or results

Citation: Indicate study title, authors, journal, date, etc.

// ----- From the Suggestion report (10/07/2022, 3:31 PM) ----- //

ATE (inhalation, gaseous) of mixture: 56250 ppmv

Skin corrosion/irritation

May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

XYLENES (MIXED): Species: Rabbit

Exposure time: 24h

Result: Irrating to skin

Acetone: Skin-Rabbi

Result: Mild Skin irritation- 24h

(Draize Test)

Remarks: (RTECS)

Serious eye damage/irritation

May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

XYLENES (MIXED): Species: Rabbit

Result: Irritating to eyes

Acetone: Eyes-Rabbit

Result: Eye irritation - 24H

(Draize Test)

Remarks: (RTECS)

Respiratory or skin sensitization

No data available.

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

XYLENES (MIXED): May be fatal if swallowed and enters airways.

Acetone: Maximization Test - Guinea Pig
Result: Not a skin sensitizer
Remarks: (ECHA)
Chronic exposure may cause dermatitis.

Germ cell mutagenicity

Acetone: Test Type: Mutagenicity (mammal cell test) : chromosome aberration.
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: Negative

Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation : with and without metabolic activation
Method: OECD Test Guideline 471
Result: Negative

Test Type: IN vitro mammalian cell gene mutation test
Test system: Mouse lymphoma test
Metabolic activation: without metabolic activation
Method: OECD Test Guideline 476
Result: Negative

Carcinogenicity

This product is or contains a component that has been reported to be carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC.
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

XYLENES (MIXED): IARC Group 2B: Possibly carcinogenic to humans
100-41-4: Ethylbenzene
98-82-8 Cumene

Reproductive toxicity

No data available

Summary of evaluation of the CMR properties

No data available.

STOT-single exposure

---Xylene---

Inhalation - May cause damage to organs through prolonged or repeated exposure. - Central nervous system, Liver, Kidney

N-Butyl acetate: 123-86-4:
Target Organs: Central Nervous system
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

STOT-repeated exposure

No data available

Aspiration hazard

Aspiration of xylene into the lungs during ingestion or vomiting may result in serious injuries to the lungs or even death. If large quantities of xylene are aspirated into the lungs, pulmonary edema, pulmonary bleeding, coma, seizures or death may occur

SECTION 12: Ecological information

No data available

Components:

Acetone: Toxicity to fish: flow-through test LC50- Pimephales promelas (fathead minnow) - 6,210 mg/l - 96 h (OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates: static test NOEC - M.aeruginosa - 530 mg/l - 8 d (DIN 38412)
Remarks: (maximum permissible toxic concentration) (IUCLID)

Toxicity to bacteria: static test EC50 - activated sludge - 61.15 mg/l -30min (OECD Test Guideline 209)

N-Butyl acetate: 123-86-4:

Toxicity to fish: LC50 (Pimephales promelas (fathead minnow)): 18 mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to daphnia and other : EC50 (Daphnia magna (WATER flea)): 44 mg/l Exposure time: 48 h Test Type:static test aquatic invertebrates

Harmful to aquatic life

This product has no known ecotoxicological effects.

Persistence and degradability

Components:

-----Xylene-----

No data available

Acetone: Biodegradability: aerobic - Exposure time 28 d

Result: 91% - Readily biodegradable

9OECD Test Guideline 301B)

Biochemical Oxygen: 1,850 mg/g

Demand (BOD): Remarks: (IUCLID)

Chemical Oxygen: 2,070 mg/g

Demand (COD) Remarks: (IUCLID)

Theoretical Oxygen: 2,200 mg/g

Demand Remarks: (Lit.)

N- Butyl Acetate

Bioaccumulative potential

Components:

Bioconcentration factor (BCF):90

XYLENES (MIXED): 98-82-8 :

Partition coefficient: log Pow 3.55 (23C)

Acetone: Does not bioaccumulate

Mobility in soil

No data available.

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects

XYLENES (MIXED): Ozone-Depletion Potential:

Regulation: 40 CFR Protection of Environment: Part 82 Protection of Stratospheric Ozone- CAA section 602 Class I substances

Acute toxicity estimate Inhalation - 4 h - 11 mg/l (Calculation method)

SECTION 13: Disposal considerations

Disposal of the product

Disposal should be in accordance with applicable Federal, State and local laws and regulations. Local regulations may be more stringent than State or Federal requirements.

Disposal of contaminated packaging

Dispose of as unused product.

Waste treatment

Waste should be minimized at all times. All waste material should be disposed of with a licensed waste disposal contractor.

SECTION 14: Transport information

DOT (US)

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint Related Material

Reportable quantity (RQ):

Marine pollutant:

Poison inhalation hazard:

IMDG

UN Number: UN1263

Class: 3

Packing Group: II

EMS Number: F-E, S-E

Proper Shipping Name: Paint Related Material

IATA

UN Number: UN1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint Related Material

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Massachusetts Right To Know Components

Chemical name: Benzene, m-dimethyl-

CAS number: 108-38-3

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER SAFETY DATA SHEET

New Jersey Right To Know Components

Common name: m-XYLENE see Fact Sheet # 2014 on XYLENE
CAS number: 108-38-3

Pennsylvania Right To Know Components

Chemical name: Benzene, 1,3-dimethyl-
CAS number: 108-38-3

Canadian Domestic Substances List (DSL)

Chemical name: Benzene, 1,3-dimethyl-
CAS: 108-38-3

New Jersey Right To Know Components

Common name: TALC (NOT CONTAINING ASBESTOS FIBERS)
CAS number: 14807-96-6

Pennsylvania Right To Know Components

Chemical name: Talc
CAS number: 14807-96-6

Canadian Domestic Substances List (DSL)

Chemical name: Talc ($Mg_3H_2(SiO_3)_4$)
CAS: 14807-96-6

Massachusetts Right To Know Components

Enter applica

New Jersey Right To Know Components

Common name: CARBON BLACK
CAS number: 1333-86-4

Pennsylvania Right To Know Components

Chemical name: Carbon black
CAS number: 1333-86-4

Canadian Domestic Substances List (DSL)

Chemical name: Carbon black
CAS: 1333-86-4

California Prop. 65 components

Chemical name: Carbon black (airborne, unbound particles of respirable size)
CAS number: 1333-86-4
02/21/2003 - Cancer

California Prop. 65 components

Chemical name: Titanium dioxide (airborne, unbound particles of respirable size)
CAS number:
09/02/2011 - Cancer

Canadian Domestic Substances List (DSL)

Chemical name: Carbonic acid calcium salt (1:1)
CAS: 471-34-1

New Jersey Right To Know Components

Common name: KAOLIN
CAS number: 1332-58-7

Pennsylvania Right To Know Components

Chemical name: Kaolin
CAS number: 1332-58-7

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

Canadian Domestic Substances List (DSL)

Chemical name: Kaolin
CAS: 1332-58-7

Canadian Domestic Substances List (DSL)

Chemical name: 2-Propenoic acid, 2-methyl-, polymer with ethenylbenzene and methyl 2-methyl-2-propenoate
CAS: 25035-81-8

Massachusetts Right To Know Components

Chemical name: Xylene (mixed isomers)
CAS number: 1330-20-7

New Jersey Right To Know Components

Common name: XYLENES
CAS number: 1330-20-7

Pennsylvania Right To Know Components

Chemical name: Benzene, dimethyl-
CAS number: 1330-20-7

Canadian Domestic Substances List (DSL)

Chemical name: Benzene, dimethyl-
CAS: 1330-20-7

SARA 311/312 Hazards

Enter applica

SARA 313 Components

Enter applica

Massachusetts Right To Know Components

Phosphoric acid
CAS number: 7664-38-2

New Jersey Right To Know Components

Phosphoric acid
CAS number: 7664-38-2

Pennsylvania Right To Know Components

Phosphoric acid
CAS number: 7664-38-2

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Canadian Domestic Substances List (DSL)

Chemical name: Phosphoric acid
CAS: 7664-38-2

Canadian Domestic Substances List (DSL)

Chemical name: 2-Propanol, 1-methoxy-, acetate
CAS: 108-65-6

Massachusetts Right To Know Components

Chemical name: Acetone
CAS number: 67-64-1

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

New Jersey Right To Know Components

Common name: ACETONE
CAS number: 67-64-1

Pennsylvania Right To Know Components

Chemical name: 2-Propanone
CAS number: 67-64-1

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Canadian Domestic Substances List (DSL)

Chemical name: 2-Propanone
CAS: 67-64-1

Massachusetts Right To Know Components

n-Butyl acetate
CAS number: 123-86-4

New Jersey Right To Know Components

n-Butyl acetate
CAS number: 123-86-4

Pennsylvania Right To Know Components

n-Butyl acetate
CAS number: 123-86-4

SARA 311/312 Hazards

Fire Hazard

Canadian Domestic Substances List (DSL)

Chemical name: Acetic acid, butyl ester
CAS: 123-86-4

Canadian Domestic Substances List (DSL)

Chemical name: Stannane, dibutylbis[(1-oxododecyl)oxy]-
CAS: 77-58-7

15.2 Chemical Safety Assessment

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

HMIS Rating

Health	2
Flammability	3
Physical hazard	0
Personal protection	G

NFPA Rating

Health hazard	2
Fire hazard	3
Reactivity hazard	0
Special hazard	

RSP DTM4200 DTM HIGH BUILD URETHANE PRIMER SURFACER

SAFETY DATA SHEET

SECTION 16: Other information

16.1 Further information/disclaimer

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer.