



SAFETY DATA SHEET

UBCLV — COLOR

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

PRODUCT IDENTIFIER _____ Urethane Basecoat — Low VOC - Color

OTHER MEANS OF IDENTIFICATION _____ Not Available — N/A

PRODUCT CODE _____ UBCLV

RECOMMENDED USE _____ Paint, Coatings

RECOMMENDED RESTRICTIONS _____ Professional Use Only

MANUFACTURER/IMPORTER/SUPPLIER _____ Not Available — N/A

DETAILS OF SUPPLIER OF THE S.D.S. _____ See sections 16 for more information

DISTRIBUTOR INFORMATION

MANUFACTURER/COMPANY NAME _____ Custom Shop

ADDRESS _____ 6251 Howdy Wells Ave., Las Vegas, NV. 89115

TELEPHONE _____ Customer Service — (858) 909-2110

EMERGENCY PHONE NUMBER _____ CHEMTREC — (800) 424-9300

SECTION 2: HAZARD(S) IDENTIFICATION

| | | |
|-------------------------------|---|-------------|
| CLASSIFICATION _____ | _____ Skin Corrosion / Irritation _____ | Category 2 |
| | _____ Serious Eye Damage/Eye Irritation _____ | Category 2 |
| | _____ Sensitization, skin _____ | Category 1 |
| | _____ Carcinogenicity _____ | Category 1A |
| | _____ Reproductive Toxicity _____ | Category 2 |
| | _____ Specific Target Organ Toxicity, Single Exposure _____ | Category 3 |
| | _____ Specific Target Organ Toxicity, Repeated _____ | Category 1 |
| | _____ Aspiration Toxicity _____ | Category 1 |
| _____ Flammable Liquids _____ | Category 2 | |

LABEL ELEMENTS _____



HAZARD STATEMENT _____ Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness.

PREVENTION _____ Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

RESPONSE _____ IF exposed or concerned: Get medical advice/attention.

EYES _____ IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

SKIN _____ If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

INHALATION _____ IF INHALED: Remove person to fresh air and keep comfortable for breathing.

INGESTION _____ IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

FIRE _____ In case of fire: Use CO2, dry chemical, or foam for extinction.

STORAGE _____ Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

DISPOSAL _____ Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) _____ Not applicable — N/A

OTHER HAZARDS _____ Harmful to aquatic life with long lasting effects. Spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

UNKNOWN ACUTE TOXICITY _____ 0% of the mixture consists of ingredient(s) of unknown toxicity.

This document represents the broadest array of ingredient composition, hazard, and precautionary information for coatings produced from specified components of this product series and mixed according to instructions. The information presented in this SDS may overstate the actual ingredients contained in and the hazards and precautionary warnings recommended for the particular coating for which it is provided.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS Number | Weight % |
|--|-------------------|-----------------|
| BENZENE, 1-CHLORO-4-(TRIFLUOROMETHYL)- | 98-56-6 | 21 - 44 |
| METHYL ACETATE | 79-20-9 | 17 - 36 |
| TITANIUM DIOXIDE | 13463-67-7 | 0 - 27 |
| N-BUTYL ACETATE | 123-86-4 | 0 - 23 |
| XYLENES | 1330-20-7 | 0 - 12 |
| METHYL N-AMYL KETONE | 110-43-0 | 0 - 6 |
| ACETONE | 67-64-1 | 2 - 6 |
| NAPHTHA, PETROLEUM, HYDROTREATED HEAVY | 64742-48-9 | 0 - 5 |
| 2-PENTANONE, 4-METHYL- | 108-10-1 | 0 - 5 |
| SOLVENT NAPHTHA, PETROLEUM, LIGHT AROMATIC | 64742-95-6 | 0 - 4 |
| ETHYLBENZENE | 100-41-4 | 0 - 3 |
| CARBON BLACK | 1333-86-4 | 0 - 3 |
| M-XYLENE | 108-38-3 | 0 - 3 |
| STODDARD SOLVENT | 8052-41-3 | 0 - 2 |
| BENZENE, 1,2,4-TRIMETHYL- | 95-63-6 | 0 - 2 |
| TOLUENE | 108-88-3 | 0 - 2 |

| Chemical Name | CAS Number | Weight % |
|----------------------|-------------|----------|
| 2-BUTANONE, OXIME | 96-29-7 | 0 - 0.3 |
| QUARTZ | 14808-60-7 | 0 - 0.2 |
| PROPRIETARY ADDITIVE | UNKOWN | 0 - 0.3 |
| PROPRIETARY ADDITIVE | PROPRIETARY | 0 - 0.3 |
| PROPRIETARY ADDITIVE | PROPRIETARY | 0 - 0.3 |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4: FIRST-AID MEASURES

GENERAL ADVICE _____ IF exposed or concerned: Get medical advice/attention.

EYE CONTACT _____ IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

SKIN CONTACT _____ If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

INHALATION _____ IF INHALED: Remove person to fresh air and keep comfortable for breathing.

INGESTION _____ IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

SYMPTOMS _____ No information available.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

NOTE TO PHYSICIANS _____ Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA _____ Dry chemical, CO2, water spray or alcohol-resistant foam.

NOT TO BE USED FOR SAFETY REASONS _ Strong water jet

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL _____

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Keep product and empty container away from heat and sources of ignition.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS _____

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses. Highly flammable liquid and vapor.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

PERSONAL PRECAUTIONS _____ Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep

people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

FOR EMERGENCY RESPONDERS _____ Use personal protection recommended in Section 8.

ENVIRONMENTAL PRECAUTIONS _____ Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

METHODS FOR CONTAINMENT _____ Prevent further leakage or spillage if safe to do so.

METHODS FOR CLEANING UP _____ Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal. Avoid discharge into drains, water courses or onto the ground.

SECTION 7: HANDLING & STORAGE

PRECAUTIONS FOR SAFE HANDLING

ADVICE ON SAFE HANDLING _____ Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

GENERAL HYGIENE CONSIDERATIONS _____ When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

STORAGE CONSIDERATIONS _____ Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

INCOMPATIBLE MATERIALS _____ Water. Bases. Strong bases. Strong oxidizing agents. Strong acids. Acids. Strong reducing agents. Alkali. Aluminum. Combustible material. Hydrazine.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETER

EXPOSURE LIMITS _____ If S* appears in the OEL table, it indicates this chemical contains a skin notation.

| CHEMICAL NAME | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---|---|--|--|
| Benzene, 1-chloro-4-(trifluoromethyl)-98-56-6 | TWA: 2.5 mg/m ³ F | TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust | |
| Methyl acetate 79-20-9 | STEL: 250 ppm TWA: 200 ppm | TWA: 200 ppm TWA: 610 mg/m ³ | IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m ³ STEL: 250 ppm STEL: 760 mg/m ³ |
| Titanium dioxide 13463 -67-7 | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust | IDLH: 5000 mg/m ³ |
| n-Butyl acetate 123-86-4 | STEL: 200 ppm TWA: 150 ppm | TWA: 150 ppm TWA: 710 mg/m ³ | IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³ |
| Xylenes 1330 -20-7 | STEL: 150 ppm TWA: 100 ppm | TWA: 100 ppm TWA: 435 mg/m ³ | |
| Methyl n-amyl ketone 110-43-0 | TWA: 50 ppm | TWA: 100 ppm TWA: 465 mg/m ³ | IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m ³ |
| Acetone 67-64-1 | STEL: 750 ppm TWA: 500 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ | IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³ |
| 2-Pentanone, 4 -methyl-108-10-1 | STEL: 75 ppm TWA: 20 ppm | TWA: 100 ppm TWA: 410 mg/m ³ | IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³ |
| Ethylbenzene 100-41-4 | TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m ³ | IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³ |
| Carbon black 1333-86-4 | TWA: 3 mg/m ³ inhalable fraction | TWA: 3.5 mg/m ³ | IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH |
| m-Xylene 108-38-3 | STEL: 150 ppm TWA: 100 ppm | TWA: 100 ppm TWA: 435 mg/m ³ | IDLH: 900 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³ |
| Stoddard solvent 8052-41-3 | TWA: 100 ppm | TWA: 500 ppm TWA: 2900 mg/m ³ | IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³ |
| Benzene, 1,2,4-trimethyl-95-63-6 | TWA: 25 ppm | | TWA: 25 ppm TWA: 125 mg/m ³ |
| Toluene 108-88-3 | TWA: 20 ppm | TWA: 200 ppm Ceiling: 300 ppm | IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³ |
| Quartz 14808-60-7 | TWA: 0.025 mg/m ³ respirable fraction | TWA: (30) / (%SiO ₂ + 2) mg/m ³ TWA total dust TWA: (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction TWA: (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction ppm | IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust |

APPROPRIATE ENGINEERING CONTROLS

ENGINEERING CONTROLS _____ Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION _____ Tight sealing safety goggles.

SKIN AND BODY PROTECTION _____ Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

HAND PROTECTION _____ There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

RESPIRATORY PROTECTION _____ When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

THERMAL PROTECTION _____ No information available.

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

- PHYSICAL STATE** _____ Liquid
- APPEARANCE** _____ No information available
- ODOR** _____ Solvent
- COLOR** _____ No information available
- ODOR THRESHOLD** _____ No information available
- pH VALUE** _____ No information available
- MELTING POINT/FREEZING POINT** _____ No information available
- BOILING POINT / BOILING RANGE** _____ 56.05 °C / 133 °F
- FLASH POINT** _____ -20 °C / -4 °F
- EVAPORATION RATE** _____ No information available
- FLAMMABILITY (SOLID, GAS)** _____ No information available
- FLAMMABILITY LIMIT IN AIR** _____
 - UPPER FLAMMABILITY LIMIT** _____ No information available
 - LOWER FLAMMABILITY LIMIT** _____ No information available
- VAPOR PRESSURE** _____ No information available
- VAPOR DENSITY** _____ No information available
- DENSITY (LBS PER US GALLON)** _____ 9.08
- SPECIFIC GRAVITY** _____ 1.09
- SOLUBILITY (IES)** _____ No information available
- PARTITION COEFFICIENT** _____ No information available
- AUTO-IGNITION TEMPERATURE** _____ No information available
- DECOMPOSITION TEMPERATURE** _____ No information available
- KINEMATIC VISCOSITY** _____ No information available
- DYNAMIC VISCOSITY** _____ No information available

OTHER INFORMATION

SECTION 10: STABILITY & REACTIVITY

REACTIVITY _____ No information available

CHEMICAL STABILITY _____ Stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS _____ None under normal processing.

CONDITIONS TO AVOID _____ Heat, flames and sparks.

INCOMPATIBLE MATERIALS _____ Water. Bases. Strong bases. Strong oxidizing agents. Strong acids. Acids. Strong reducing agents. Alkali. Aluminum. Combustible material. Hydrazine.

HAZARDOUS

DECOMPOSITION PRODUCTS _____ Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Hydrogen Chloride. Oxides of sulfur. Chlorine.

SECTION 11: TOXICOLOGICAL INFORMATION

INFORMATION ON LIKELY ROUTES OF EXPOSURE

EYE CONTACT _____ Causes serious eye irritation.

SKIN CONTACT _____ Causes skin irritation. May cause an allergic skin reaction.

INGESTION _____ May be fatal if swallowed and enters airways.

INHALATION _____ May cause respiratory irritation. May cause drowsiness or dizziness.

NUMERICAL MEASURES OF TOXICITY — COMPONENT INFORMATION

| CHEMICAL NAME | ORAL LD50 | DERMAL LD50 | INHALATION LC50 |
|---|------------------------|---------------------------|--|
| Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6 | = 13 g/kg (Rat) | > 2 mL/kg (Rabbit) | = 33 mg/L (Rat) 4 h |
| Methyl acetate 79-20-9 | > 5,000 mg/kg (Rat) | > 5 g/kg (Rabbit) | = 16,000 ppm (Rat) 4 h |
| Titanium dioxide 13463 -67-7 | > 10,000 mg/kg (Rat) | | |
| n-Butyl acetate 123-86-4 | = 14.13 mg/kg (Rat) | > 17,600 mg/kg (Rabbit) | = 390 ppm (Rat) 4 h |
| Xylenes 1330 -20-7 | = 3,500 mg/kg (Rat) | > 4,350 mg/kg (Rabbit) | = 29.08 mg/L (Rat) 4 h |
| Methyl n-amyl ketone 110-43-0 | = 1,600 mg/kg (Rat) | = 12.6 mL/kg (Rabbit) | > 2,000 ppm (Rat) 4 h |
| Acetone 67-64-1 | | | = 50,100 mg/m ³ (Rat) 8 h |
| Naphtha, petroleum, hydrotreated heavy 64742 -48-9 | > 5,000 mg/kg (Rat) | > 3,160 mg/kg (Rabbit) | |
| 2-Pentanone, 4 -methyl- 108-10-1 | = 2,080 mg/kg (Rat) | = 3,000 mg/kg (Rabbit) | = 8.2 mg/L (Rat) 4 h |
| Solvent naphtha, petroleum, light aromatic 64742 -95-6 | | > 2,000 mg/kg (Rabbit) | = 3,400 ppm (Rat) 4 h |
| Ethylbenzene 100-41-4 | = 3,500 mg/kg (Rat) | = 15,400 mg/kg (Rabbit) | = 17.2 mg/L (Rat) 4 h |
| Carbon black 1333-86-4 | | | |

| CHEMICAL NAME | ORAL LD50 | DERMAL LD50 | INHALATION LC50 |
|--------------------------------------|-----------------------|---------------------------|-----------------------------------|
| m-Xylene 108-38-3 | = 5,000 mg/kg (Rat) | | |
| Stoddard solvent 8052-41-3 | | | |
| Benzene, 1,2,4-trimethyl- 95-63-6 | = 3,280 mg/kg (Rat) | > 3,160 mg/kg (Rabbit) | = 18 g/m ³ (Rat) 4 h |
| Toluene 108-88-3 | = 2,600 mg/kg (Rat) | = 12,000 mg/kg (Rabbit) | = 12.5 mg/L (Rat) 4 h |
| 2-Butanone, oxime 96-29-7 | = 930 mg/kg (Rat) | = 0.2 mg/kg (Rabbit) | = 20 mg/L (Rat) 4 h |
| Proprietary Additive UNKNOWN | | | |
| Proprietary Additive | | | |
| Proprietary Additive | = 2,615 mg/kg (Rat) | | |

NUMERICAL MEASURES OF TOXICITY — PRODUCT INFORMATION

THE FOLLOWING VALUES ARE CALCULATED BASED ON CHAPTER 3.1 OF THE GHS DOCUMENT

- ATEMIX (ORAL) _____ 8,472 Mg/kg
- ATEMIX (DERMAL) _____ 8,113 Mg/kg
- ATEMIX (INHALATION-DUST/MIST) _ 5.3 mg/l
- ATEMIX (INHALATION-VAPOR) ____ 39 mg/l

UNKNOWN ACUTE TOXICITY _____ 0% of the mixture consists of ingredient(s) of unknown toxicity.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE

CARCINOGENICITY _____ According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials. According to IARC, Volume 93, no significant exposure to primary particles of carbon black is thought to occur from use in paints since the pigment is bound to other materials.

| CHEMICAL NAME | ACGIH | IARC | NTP | OSHA |
|---------------------------------------|-------|----------|-------|------|
| Titanium dioxide 13463-67-7 | | Group 2B | | X |
| 2-Pentanone, 4-methyl- 108-10-1 | A3 | Group 2B | | X |
| Ethylbenzene 100-41-4 | A3 | Group 2B | | X |
| Carbon black 1333-86-4 | A3 | Group 2B | | |
| Quartz 14808-60-7 | A2 | Group 1 | Known | X |

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen. A3 - Animal Carcinogen.

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans. Group 2B - Possibly Carcinogenic to Humans.

NTP (National Toxicology Program)

Known - Known Carcinogen.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

SKIN CORROSION/IRRITATION _____ Causes skin irritation

SERIOUS EYE DAMAGE/EYE IRRITATION _ Causes serious eye irritation

SKIN SENSITIZATION _____ May cause an allergic skin reaction

RESPIRATORY SENSITIZATION _____ Not applicable

GERM CELL MUTAGENICITY _____ Not applicable

CARCINOGENICITY _____ May cause cancer

REPRODUCTIVE TOXICITY _____ Suspected of damaging fertility or the unborn child

SPECIFIC TARGET ORGAN

TOXICITY (SINGLE EXPOSURE) _____ May cause respiratory irritation May cause drowsiness or dizziness

SPECIFIC TARGET ORGAN

TOXICITY (REPEATED EXPOSURE) _____ Causes damage to organs through prolonged or repeated exposure

ASPIRATION HAZARD _____ Not applicable

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY _____ Harmful to aquatic life with long lasting effects.

ENVIROMENTAL PRECAUTIONS _____ Prevent product from entering drains.

PERSISTENCE AND DEGRADABILITY ____ No information available

BIOACCUMULATION _____ No information available

MOBILITY _____ No information available

OTHER ADVERSE EFFECTS _____ No information available

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

DISPOSAL OF WASTES _____ Disposal should be in accordance with applicable regional, national and local laws and regulations.

CONTAMINATED PACKAGING _____ Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

SECTION 14: TRANSPORT INFORMATION

| | <u>DOT</u> | <u>IMDG</u> | <u>IMDG</u> |
|---|--|---------------|-------------|
| 14.1 UN/ID NO | UN1263 | UN1263 | UN1263 |
| 14.2 PROPER SHIPPING NAME | PAINT | PAINT | PAINT |
| 14.3 HAZARD CLASS | 3 | 3 | 3 |
| 14.4 PACKING GROUP | II | II | II |
| 14.5 ENVIROMENTAL HAZARD | N/A | | |
| 14.6 SPECIAL PROVISIONS | 149, B52, IB2, T4, TP1, TP8, TP28 | 163 | A3, A72 |
| | EMERGENCY RESPONSE GUIDE NUMBER | EmS-No | |
| | 128 | F-E, S-E | |
| 14.7 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE | | | N/A |

SECTION 15: REGULATORY INFORMATION

INTERNATIONAL INVENTORIES

TSCA - UNITED STATES TOXIC SUBSTANCES CONTROL ACT SECTION 8(b) INVENTORY

ALL COMPONENTS ARE LISTED OR EXEMPT FROM LISTING

US FEDERAL REGULATIONS

| CHEMICAL NAME | TSCA - TOXIC SUBSTANCE CONTROL ACT, SECTION 12(b) EXPORT NOTIFICATION |
|--|---|
| Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6 | Section 4 |

| CHEMICAL NAME | SARA 313 - THRESHOLD VALUES % | HAZARDOUS AIR POLLUTANTS (HAPs) CONTENT |
|---|-------------------------------|---|
| Xylenes 1330-20-7 0 - 12 | 1 | Present |
| Aluminum 7429-90-5 0 - 7 | 1 | |
| 2-Pentanone, 4-methyl- 108-10-1 0 - 5 | 1 | Present |
| Ethylbenzene 100-41-4 0 - 3 | 0.1 | Present |
| m-Xylene 108-38-3 0 - 3 | 1 | Present |
| C.I. Pigment Yellow 129 15680-42-9 0 - 2 | 1 | |
| Benzene, 1,2,4-trimethyl- 95-63-6 0 - 2 | 1 | |
| Toluene 108-88-3 0 - 2 | 1 | Present |
| PROPRIETARY COPPER COMPOUND UNKNOWN 0 - 2 | 1.0 | |

SARA 311/312 HAZARD CATEGORIES

ACUTE HEALTH HAZARD _____ Yes

CHRONIC HEALTH HAZARD _____ Yes

FIRE HAZARD _____ Yes

SUDDEN RELEASE OF PRESSURE HAZARD _ No

REACTIVE HAZARD _____ Yes

| CHEMICAL NAME | CWA - REPORTABLE QUANTITIES | CWA - TOXIC POLLUTANTS | CWA - PRIORITY POLLUTANTS | CWA - HAZARDOUS SUBSTANCES |
|-----------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| n-Butyl acetate 123-86-4 | 5,000 lb | | | X |
| Xylenes 1330-20-7 | 100 lb | | | X |
| Ethylbenzene 100-41-4 | 1,000 lb | X | X | X |
| m-Xylene 108-38-3 | 100 lb | | | |
| Toluene 108-88-3 | 1,000 lb | X | X | X |

| CHEMICAL NAME | HAZARDOUS SUBSTANCES RQs | CERCLA/SARA RQ | REPORTABLE QUANTITY (RQ) |
|--------------------------------------|--------------------------|----------------|--|
| n-Butyl acetate 123 -86-4 | 5,000 lb | | RQ 5,000 lb nal RQ RQ 2,270 kg nal RQ |
| Xylenes 1330 -20-7 | 100 lb | | RQ 100 lb nal RQ RQ 45.4 kg nal RQ |
| Acetone 67-64-1 | 5,000 lb | | RQ 5,000 lb nal RQ RQ 2,270 kg nal RQ |
| 2-Pentanone, 4 -methyl- 108 -10-1 | 5,000 lb | | RQ 5,000 lb nal RQ RQ 2,270 kg nal RQ |
| Ethylbenzene 100 -41-4 | 1,000 lb | | RQ 1,000 lb nal RQ RQ 454 kg nal RQ |
| m-Xylene 108-38-3 | 1,000 lb | | RQ 1,000 lb nal RQ RQ 454 kg nal RQ |
| Toluene 108 -88-3 | 1,000 lb | | RQ 1,000 lb nal RQ RQ 454 kg nal RQ |

US STATE REGULATIONS

RULE 66 STATUS OF PRODUCT _____ Photochemically reactive.

CALIFORNIA PROPOSITION 65 _____ WARNING! This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

U.S. EPA LABEL INFORMATION _____ **EPA PESTICIDE REGISTRATION NUMBER:** N/A

U.S. STATE RIGHT-TO-KNOW REGULATIONS

| CHEMICAL NAME | CHEMICAL NAME |
|--|---|
| Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6 | Proprietary Non-Hazardous Ingredient–Proprietary CAS |
| Methyl acetate 79-20-9 | C.I. Pigment Blue 15 147-14-8 |
| Titanium dioxide 13463-67-7 | Proprietary Non-Hazardous Ingredient–Proprietary CAS |
| n-Butyl acetate 123-86-4 | Acetone 67-64-1 |
| Proprietary Non-Hazardous Ingredient–Proprietary CAS | Proprietary Non-Hazardous Ingredient–Proprietary CAS |
| Proprietary Inert | Naphtha, petroleum, hydrotreated heavy 64742-48-9 |
| Proprietary Non-Hazardous Ingredient–Proprietary CAS | 2-Pentanone, 4-methyl- 108-10-1 |
| Proprietary Non-Hazardous Ingredient–Proprietary CAS | Proprietary Non-Hazardous Ingredient–Proprietary CAS |
| Xylenes 1330-20-7 | Proprietary Non-Hazardous Ingredient–Proprietary CAS |
| Proprietary Non-Hazardous Ingredient–Proprietary CAS | Proprietary Non-Hazardous Ingredient–Proprietary CAS |
| Proprietary Non-Hazardous Ingredient–Proprietary CAS | Proprietary Non-Hazardous Ingredient–Proprietary CAS |
| Iron oxide (Fe2O3) 1309-37-1 | Proprietary Non-Hazardous Ingredient–Proprietary CAS |
| Proprietary Non-Hazardous Ingredient–Proprietary CAS | Solvent naphtha, petroleum, light aromatic 64742-95-6 |
| Proprietary Non-Hazardous Ingredient–Proprietary CAS | Ethylbenzene 100-41-4 |
| Proprietary Non-Hazardous Ingredient–Proprietary CAS | Carbon black 1333-86-4 |
| Proprietary Non-Hazardous Ingredient–Proprietary CAS | m-Xylene 108-38-3 |
| Proprietary Non-Hazardous Ingredient–Proprietary CAS | Barium sulfate 7727-43-7 |
| Aluminum 7429-90-5 | C.I. Pigment Yellow 129 15680-42-9 |
| Proprietary Non-Hazardous Ingredient–Proprietary CAS | Stoddard solvent 8052-41-3 |
| Proprietary Non-Hazardous Ingredient–Proprietary CAS | Benzene, 1,2,4-trimethyl- 95-63-6 |
| C.I. Pigment Green 7 1328-53-6 | Toluene 108-88-3 |
| C.I. Pigment Green 36 14302-13-7 | 2-Butanone, oxime 96-29-7 |
| Methyl n-amyl ketone 110-43-0 | Quartz 14808-60-7 |

SECTION 16: OTHER INFORMATION

HMIS

HEALTH HAZARDS

CHRONIC HEALTH HAZARD ___ 3*

FLAMMABILITY _____ 3

PHYSICAL HAZARDS _____ 1

PERSONAL PROTECTION _____ X

SUPPLIER ADDRESS _____ 6251 Howdy Wells Ave. Las Vegas, NV. 89115

PREPARED BY _____ Product Stewardship

REVISION DATE _____ 15-November-2024

REVISION NOTE _____ N/A

DISCLAIMER _____ The information on this Safety Data Sheet (SDS) is based on the present date of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

END OF SAFETY DATA SHEET (SDS)